



## CANGINI **BETONMIXER SKOVL**


TYPE	KAPACITET	BREDDE	VEJL. UDSALGSPRIS
<b>MIX150SF</b>	150 l	1258 mm	39.795 kr.
<b>MIX200SF</b>	200 l	1370 mm	41.295 kr.
<b>MIX250SF</b>	250 l	1620 mm	42.895 kr.
<b>MIX350SF</b>	350 l	1630 mm	46.295 kr.
<b>MIX450SF</b>	450 l	1946 mm	49.895 kr.
<b>MIX600SF</b>	600 l	2018 mm	60.795 kr.
<b>MIX800SF</b>	800 l	2220 mm	75.295 kr.
<b>MIX1000SF</b>	1000 l	2420 mm	87.795 kr.
<b>MIX1200SF</b>	1200 l	2420 mm	99.995 kr.

# MIXING BUCKET SAFE DISCHARGE

**PATENTED**  
**HB400**



GEARBOX TRANSMISSION DELIVERS HIGH PERFORMANCE AND DOES NOT REQUIRE CONTINUOUS MAINTENANCE INTERVENTIONS. THE USE OF DUAL CROSS RELIEF AND FLOW DIVIDER VALVES GRANTS EFFECTIVENESS AND RELIABILITY EVEN IN THE MOST DIFFICULT WORK CONDITIONS.



	MIX 1500SF	MIX 2005F	MIX 2505F	MIX 3505F	MIX 4505F	MIX 6005F	MIX 8005F	MIX 10005F	MIX 12005F
<b>A</b> MM (IN)	1000 (39)	1100 (43)	1350 (53)	1350 (53)	1670 (66)	1750 (69)	1830 (72)	2000 (79)	2000 (79)
<b>B</b> MM (IN)	1258 (50)	1370 (54)	1620 (64)	1630 (64)	1946 (77)	2018 (79)	2220 (87)	2420 (95)	2420 (95)
<b>C</b> MM (IN)	620 (24)	650 (26)	650 (26)	720 (28)	720 (28)	835 (33)	910 (36)	990 (39)	1100 (43)
<b>D</b> MM (IN)	530 (21)	580 (23)	610 (24)	680 (27)	680 (27)	800 (31)	840 (33)	910 (36)	980 (39)
WG COUPLER	KG (LB)	225 (496)	280 (612)	320 (705)	370 (816)	425 (937)	525 (1158)	675 (1488)	850 (1874)
	KG (LB)	570 (1257)	740 (1637)	895 (1973)	1175 (2590)	1460 (3219)	1905 (4200)	2515 (5545)	3150 (6944)
	L (GAL)	150 (39.6)	200 (52.9)	250 (66)	350 (92.5)	450 (118.9)	600 (158.5)	800 (211.3)	1000 (264.2)
DISCHARGE PIPE	MM (IN)	180 (7)	210 (8)	210 (8)	210 (8)	210 (8)	210 (8)	210 (8)	210 (8)
MAX	L/MIN (GAL/MIN)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	100 (26)
MAX	BAR (PSI)	200 (2907)	200 (2907)	200 (2907)	200 (2907)	200 (2907)	200 (2907)	200 (2907)	200 (2907)



## STANDARD TECHNICAL FEATURES

- SAFE LOCKING/DISCHARGE**  
THE OPERATOR LOCKS THE DISCHARGE PIPE FROM THE BUCKET'S SIDE IN THE SAFEST WORK CONDITION.
- CONTROL ROD FOR THE DISCHARGE PIPE**  
IT ENABLES THE PIPES DISPLACEMENT FOR THE SIDE POURING.
- FIXING SYSTEM FOR THE DISCHARGE PIPE**  
IT ALLOWS TO FIX THE PIPE IN ITS POSITION OF SIDE DISCHARGE.
- SAFE AUGER IN HB400**  
WHEN THE GRID IS OPENED AN AUTOMATIC SYSTEM STOPS THE AUGER'S ROTATING MOVEMENT.
- AUGER REMOVAL**  
THE BUCKET'S BODY HAS BEEN DESIGNED IN A SUCH WAY THAT THE ENTIRE AUGER CAN BE REMOVED THUS MAKING THE MAINTENANCE OPERATION EASIER.
- GEARMOTOR**  
IT GUARANTEES HIGH PERFORMANCES TO THE ENTIRE SYSTEM.
- ELECTRIC KIT**  
IT ALLOWS THE CONTROL BOTH OF THE MIXING AND THE DISCHARGE OPERATIONS FROM THE CAB.

## OPTIONAL

- FLOW-REVERSAL VALVE**  
IT ALLOWS TO MAKE THE HYDRAULIC FLOW BI-DIRECTIONAL AND TO USE THE BUCKET ALSO ON MACHINES WITH UNIDIRECTIONAL SYSTEM.
- COUPLING SYSTEM FOR WHEEL LOADERS, BACKHOE LOADERS AND TELESCOPICS**  
THE WHEEL LOADER COUPLING PLATE CAN BE ADDED TO THE STANDARD SKID COUPLING SYSTEM.