

Technical sheet :

# **ME 316**

---




Technical characteristics			Metric
1.1	Manufacturer		Manitou
1.2	Model Name		ME 316
1.3	Power source		Electric
1.4	Operator type		Seated
1.5	Max. capacity	Q	1600 kg
1.6	Load centre of gravity	c	500 mm
1.8	Load distance, centre of drive axle to fork	x	355 mm
1.9	Wheelbase	y	1358 mm
Weight			
2.1	Service Weight		3120 kg
2.2	Weight on front axle (laden) / rear axle (laden)		4100 kg / 620 kg
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		1440 kg / 1680 kg
Wheels			
3.1	Tyres type		Super Elastic
3.2	Dimensions of front wheels		18x7-8
3.3	Dimensions of rear wheels		15x4,5-8
3.5	Number of front wheels / rear wheels		2 / 1
3.2	Number of drive wheels		2
3.6	Front wheel gauge	b10	910 mm
3.7	Rear wheel	b11	175 mm
Dimensions			
4.1	Tilt of Mast Forward (deg) / Backward (deg)	$\alpha / \beta$	5.5 / 6.5
4.7	Height of overhead guard (cabin)	h6	2040 mm
4.8	Seat height/stand height	h7	1000 mm
4.12	Height of towing bar (coupling height)	h10	500 mm
4.19	Overall length	l1	2968 mm
4.20	Length to face of forks	l2	1898 mm
4.21	Overall width	b1	1086 mm
4.22	Forks section / width / length	s / e / l	35 mm x 100 mm x 1070 mm
4.23	Fork carriage ISO 2328 (class/form) A/B		FEM 2A
4.24	Fork carriage width	b3	1000 mm
4.31	Ground clearance below mast	m1	100 mm
4.32	Ground clearance at centre of wheelbase	m2	110 mm
4.35	Turning radius	Wa	1555 mm
Performances			
5.1	Travel speed (laden / unladen)		16 km/h / 18 km/h
5.2	Lifting speed (laden / unladen)		0.4 Nm / 0.47 Nm
5.3	Lowering speed (laden / unladen)		0.46 Nm / 0.44 Nm
5.5	Drawbar pull (Laden / Unladen)		750 daN / 772
5.7	Gradeability - laden / unladen (%)		16 % / 18
5.10	Service brake		Oil bath
Engine			
6.1	Drive motor rating S2 60 min		9.5 kW
6.2	Lift motor rating at S3 15%		8.6 kW

Engine			
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN43531 A
6.4	Battery / Batteries capacity		48 V / 575 A
7.2	Engine power according to ISO 1585		9.5 kW
7.5	Fuel consumption according to VDI cycle		4,3
Miscellaneous			
8.1	Type of drive control		Electronic
8.2	Working hydraulic pressure for attachments (bar)		180 Bar
8.3	Oil flow rate for attachments (l/min)		35
8.4	Measured/guaranteed mean noise level at the ear of the operator		70







Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508  
RCS Nantes